




HLX-SESS PRO

- 0.5C Continuous Power
- Ultra safe LFP material
- Wide range inverter compatibility
- Active balancing charging, low self consumption
- years warranty 10

Model	
Cell Type	LFP
Rated Power	14.3kWh
Rated Capacity	280Ah
Rated Voltage	51.2V
Charge Voltage (Vdc)	56.5V
Battery Charge Current (A)	140 (max. continuous) 150 (start limit current to 10A, retest every 10 mihutes) 160 (peak1 15S) 180 (peak2 500ms)
Battery DisCharge Current (A)	140 (max. continuous) 150 (start giving over-current alarm but not stop discharging) 160 (peak1 5minutes) 200 (peak2 500ms)
Parallel	Up to 32 units parallelable w/o extra device needed, slave battery drops offline or come back alive does not affect system running
IP Level	IP20
Dimension (W*H*D)	475*900*238mm / 18.7*35.4*9.4 in
Weight	115kg / 253.5lbs
Communication	CAN/RS485
Robust Applications	Auto-addressing and stronger protection
DOD	90%
Cycles	8000
Compatible Inverter	Victron, Luxpower, Deye, Voltronic, SMA Goodwe, Growatt, Sofar, Solark, SRNE, Must
Humidity	5%~85% RH (No condensation)
Work Temperature	-20 ~ +55 ℃
Storage Temperature	-10 ~ +35 ℃
Remote Maintenance	Flexible remote upgrade, Original firmware backup to prevent upgrade failure
Warranty *	10 years, 8000 cycles
Certification	CE UN38.3; IEC62619
Protection	Overcharge/discharge/current/voltage/temperature protection Short circuit protection, Reverse connection protection Charge balance, Low SOC protection

@25℃, 90% DOD. 0.5C testing condition